

✓

Patent Abstracts of Japan

PUBLICATION NUMBER : 09241437
PUBLICATION DATE : 16-09-97

APPLICATION DATE : 08-03-96
APPLICATION NUMBER : 08051591

APPLICANT : MITSUBISHI CHEM CORP;

INVENTOR : YOSHIKIYO TETSUYA;

INT.CL. : C08L 23/08 C09D123/08 //(C08L 23/08 , C08L 23:06), (C09D123/08 , C09D123:06)

TITLE : POLYETHYLENE COMPOSITION FOR APPLYING STEEL PIPE

ABSTRACT : PROBLEM TO BE SOLVED: To obtain a polyethylene composition for applying steel pipe, excellent in low-temperature physical property and environmental stress cracking resistance (ESCR) and improved in penetration at high temperature.

SOLUTION: This polyethylene composition for applying steel pipe contains 60-90wt.% linear low density polyethylene having 0.1-1.5e/10 min melt index and $\geq 1,000$ hr environmental stress cracking resistance (ESCR) and $\geq 200\%$ tensile elongation at break at -45°C and 10-40 wt.% high density polyethylene having $\leq 1\text{g}/10$ min melt index, ≥ 50 fluidity ratio and $\geq 0.94\text{g}/\text{cm}^3$ density.

COPYRIGHT: (C)1997,JPO